


~~CONFIDENTIAL~~

NACA RM No. L7L22

RM L7L22

53-32-27



TECH LIBRARY KAFB, NM

RESEARCH MEMORANDUM

EFFECT OF A PILOT'S CANOPY ON THE DRAG OF AN NACA RM-2
 DRAG RESEARCH MODEL IN FLIGHT AT TRANSONIC
 AND SUPERSONIC SPEEDS

By

Paul E. Purser

Langley Memorial Aeronautical Laboratory
 Langley Field, Va.

~~CONFIDENTIAL~~

This document contains classified information affecting the National Defense of the United States within the meaning of the Espionage Act, USC 50:31 and 32. Its transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law. Information so classified may be imparted only to persons in the military and naval services of the United States, appropriate civilian officials and employees of the Federal Government who have a legitimate interest therein, and to United States citizens of known loyalty and discretion who of necessity must be informed thereof.

**NATIONAL ADVISORY COMMITTEE
 FOR AERONAUTICS**

WASHINGTON

April 20, 1948

~~CONFIDENTIAL~~

319.98/13

7120

Classification changed (to: changed to Unclassified ✓

By Auth: Nasa Tech Pub Announcement #94
(OR AUTHORIZED TO CHANGE)

By NK 11 Jan 56

GRADE OF OFFICER MAKING CHANGE)

7 Apr 61
DATE

~~CONFIDENTIAL~~48-2668
TECH LIBRARY KAFB, NM

0143963

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

RESEARCH MEMORANDUM

EFFECT OF A PILOT'S CANOPY ON THE DRAG OF AN NACA RM-2

DRAG RESEARCH MODEL IN FLIGHT AT TRANSONIC

AND SUPERSONIC SPEEDS

By Paul E. Purser

1. Results of flight tests of an NACA RM-2 drag research model equipped with a pilot's canopy are presented for the Mach number range from 0.85 to 1.4. The corresponding Reynolds number range was from 30×10^6 to 48×10^6 based on the over-all length of the model. The basic body was a pointed cylinder having a nose fineness ratio of 5.0, an over-all fineness ratio of 12.8, and three stabilizing fins. The canopy was similar to those used on present-day high-speed airplanes, had a fineness ratio of about 7, and added about 10 percent to the maximum frontal area of the body. Details of the model are shown in figures 1 to 3.

2. The drag data were obtained by the Langley Pilotless-Aircraft Research Division at its testing station at Wallops Island, Va., by means of the standard NACA RM-2 technique (reference 1) and are presented in figure 4. The canopy added an almost constant increment in drag coefficient of approximately 0.08 (based on the frontal area of the basic body, 0.1364 sq ft) in the Mach number range from 1.0 to 1.4. When the drag coefficients of the canopy-equipped model are based on the frontal area of that model (0.1511 sq ft), they are still 5 to 9 percent higher than for the basic model.

Langley Memorial Aeronautical Laboratory
National Advisory Committee for Aeronautics
Langley Field, Va.

REFERENCE

1. Katz, Ellis R.: Results of Flight Tests at Supersonic Speeds to Determine the Effect of Body Nose Fineness Ratio on Body and Wing Drag. NACA RM No. L7B19, 1947.

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~*Boattail Profile*

<i>Distance from nose</i>	<i>Body diameter</i>
57.438	5.00
58.438	4.96
59.438	4.88
60.438	4.66
61.438	4.40
62.438	4.00
63.000	3.50


~~CONFIDENTIAL~~

Figure 1.-General arrangement of NACA RM-2 model equipped with pilot's canopy. All dimensions are inches.

Canopy Section

		Sta.				
		14.28	15.45	16.49	17.84	19.09
R ₂		0.215	0.500			
R ₄		.278	.521			
R ₆		.375	.570			
Y	X					
3.32				0.695		
3.25	.540	.744	.792			
3.10	.646	.827	.862			
3.02	.730	.883	.910			
2.79	.799	.931	.952			
2.63	.818	.959	.980			
2.48	.890	.980	1.001			
2.33	.924	.994	1.008			
2.17	.938	.997	1.008			
2.02	.945	1.001	1.008			
3.26				0.695		
3.11				.771		
2.95				.834		
2.79				.890		
2.64				.924		
2.49				.952		
2.34				.973		
2.18				.987		
3.22					0.396	
3.06					.528	
2.91					.619	
2.76					.688	
2.61					.744	
2.45					.785	
2.29					.813	
X	Y					
.076			3.86			
.153			3.84	3.73	3.38	
.229			3.82			
.306			3.79	3.67	3.29	
.383			3.77			
.466				3.56		
.619				3.38		

CONFIDENTIAL

Body and Canopy Profile

Sta.	R _b	H	R _f
3.571	2.61		
7.142	1.15		
10.714	1.58		
14.28	1.96	3.52	.705
14.91		3.74	
15.45		3.82	.813
16.48		3.86	.862
17.36	2.26		
17.44		3.80	
17.83		3.76	.931
19.99		3.41	1.04
21.30		3.17	
21.43	2.44		
23.23		2.82	
25.00	2.50		
25.16		2.50	





Figure 2.- Details of body nose and canopy
All dimensions are inches.


~~CONFIDENTIAL~~



(a) Top view.



(b) Side view.



~~CONFIDENTIAL~~ (c) Three-quarter front view.

Figure 3.- Photographs of NACA RM-2 model equipped with a pilot's canopy.

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18




Figure 4.- Drag data for an NACA RM-2 model with and without pilot's canopy. Rocket model flight tests.